



AIB-VINÇOTTE International s.a. / n.v.
SAFETY, QUALITY, ENVIRONMENT
Member of the Group AIB-VINÇOTTE
Head office : Boulevard A. Reyers 80 - B-1030 Brussels

VINÇOTTE - CERTEST PRODUCTS

Cross Point - Leuvensesteenweg 248 / B-1800 Vilvoorde
Tel. : +32(0)2 674.57.50 - Fax : +32(0)2 674.57.85
E-Mail : avi.conformity.marks@vincotte.be

EC TYPE EXAMINATION CERTIFICATE

No. Z 14-258-170-B

Issued by AIB-VINÇOTTE International (N°0026)

For the product(s) described hereafter :

Product group	MACHINERY
Product family	For lifting of persons
Make :	Power Climber
Type(s) :	SHERPA –SD4
Particularities :	Lift for Wind Turbines

Conformity examination requested by :

vincotte

POWER CLIMBER
Satenrozen 7
B 2550 KONTICH

Ⓔ **Criteria for certification :** Machinery Directive 2006/42/EC



Validity of the certificate : From 12/05/2016 till 12/05/2021

Conclusions of the examination :

The products comply with the above mentioned certification criteria, as confirmed by the test report of AVI no AUD/03/60570653/00/NL/001

This certificate of conformity is based on test results of one sample of the presented product, in accordance with the applicable specific criteria. It includes no appreciation of all the manufactured products, nor a statement of conformity with any other criteria that are not explicitly mentioned in this report.

This certificate is issued in English.

Brussels, 12/05/2016

0001

Tom Derveaux
Contract Manager Design Review

Christian Lefebvre.
President of the certification Committee

Ⓔ **Annex(es) :** Description of the certified product(s) : (1 Page)

V-CERTCONF-e

POWER CLIMBER

SHERPA- SD4

CHARACTERISTICS	VALUES
Main platform Dimensions (m)	0.95 x 0.6
Rated load (kg) /Nb. of persons max	240 / 2 pers.
Max working height (m)	200 m
Hoisting speed (m/min)	17
Self weight platform	Max. 160 kg
Hoist wire rope Diameter	8.4 mm
Guide wire rope Diameter	12 mm
Power supply voltage	3*690V : (50 Hz / 60 Hz) +E 3* 400V (50 Hz / 60 Hz) +E
Power motor	1 x 1.3 Kw
Control system:	230 V ac
Noise level (dB (A))	Max. 70 dBA

Available options:

- Right or Left Sliding door
- Tension system for wire ropes guiding system:
 - o Tension system above Floor
 - o Tension system underneath Floor connect on T-Beam
 - o Tension system underneath Floor
- Depending on the tower layout, option for emergency step is available or required.
- The lift is designed for access from ground level to top level and vice versa as normal use, option for safezone detection at intermediate platforms.
- Call Send Box
- Extra Emergency stop box
- Supply cable system:
 - o Storage Bin System
 - o Cable loop System
- Top obstruction system
- Back retainer system in combination with Top obstruction system
- Top retainer system in combination with Top obstruction system
- Bottom & top landing platforms, intermediate platforms (design)